

# FLUIDE G3



**Fluid for automatic transmissions and hydraulic systems.**

## USES

- Is recommended for all automatic transmissions and hydraulic systems for which the manufacturer recommends a DEXRON® III fluid :
- automatic gearboxes
- couplers and convertors
- power-assisted steering systems.

## PROPERTIES

- Very high thermal stability, high antioxidant and detergent level
- Special friction properties giving controlled slip for friction components : gear shifting quality, demands smooth clutching action without excessive slip and free from chatter.
- High antiwear, anticorrosion and antifoam performances.
- Perfect neutrality with elastomers and non-ferrous metals (copper , etc...).
- Very high viscosity index.
- Low temperature fluidity to avoid surge or sudden overload of circuits when starting in very cold weather.
- Precise and smooth automatic shifting even at very low speed.

## CHARACTERISTICS

FLUIDE G3	Units	
Density at 15 °C	kg/L	0,861
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	33.3
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	7,1
Dyn. Viscosity Brookfield at -40°C	MPa.s	< 20 000
Pour point	°C	-45

*The typical characteristics mentioned represent mean values.*

## PERFORMANCES

Level GM DEXRON III et FORD MERCON®  
ALLISON C4  
MAN 339 type F  
VOITH 55.6335.32 (old G 607)  
ZF TE-ML 03D, 04D, 09, 14A, 17C  
MB page 236.5 et 236.9

**TOTAL LUBRIFIANTS**  
16, rue de la République  
92800 PUTEAUX

**FLUIDE G3**  
N° MGP/10/04  
October 2004



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard  
A safety data file conforming to the requirements of current EU legislation is available from your local trade consultant