

FLUIDE II D



Fluid for automatic transmissions and hydraulic systems.

USES

- Automatic or semi-automatic transmissions and torque converters of passenger cars, light commercial vehicles and industrial vehicles, when the manufacturer requires an ATF (Automatic Transmission Fluid) GM DEXRON®-IID.
- Manual gear boxes when an ATF fluid is required.
- Hydrostatic transmissions.
- Power steering.
- Hydraulic systems when a fluid type GM DEXRON®-IID is required.

PROPERTIES

- Very high viscosity index linked with an excellent viscosity stability in operation.
- Very low pour point.
- Very good thermal stability.
- Excellent resistance to oxidation.
- Friction properties specific to the requirements of GENERAL MOTORS Hydramatic.

CHARACTERISTICS

FLUIDE II D	Unit	
Volumetric mass at 15°C	kg/m ³	870
Colour	-	Red
Viscosity at 40°C	mm ² /s	36.8
Viscosity at 100°C	mm ² /s	7.2
Viscosity index	-	163
Viscosity at -40°C	mPa.s	47500
Flash point Cleveland	°C	210
Pour point	°C	-44

The typical characteristics mentioned represent mean values.

PERFORMANCES

BMW group 23 - 3.0
BMW group 24 - 3.0
Meets the specification CATERPILLAR TO-2
GENERAL MOTORS 6137M-78 (DEXRON®-IID : former licence n° D-20356)
VOITH 55.6335.32 (former G 607)
ZF TE-ML 04D, 09, 11A, 17C

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX

FLUIDE II D
January 2004



Ce lubrifiant utilisé selon nos recommandations et pour l'application pour laquelle il est prévu ne présente pas de risque particulier.
Une fiche de données de sécurité conforme à la législation en vigueur dans la C.E. est disponible auprès de votre conseiller commercial.