

TOTAL QUARTZ 9000 0W30

Issue: 1

Page:1/7

Date: 17/07/2000

PRODUCT LABELS

Product code: P181-0000567-26

LABELLING (standard or EU) Not applicable TRANSPORT LABELLING: Not applicable

1. Product and company identification

Commercial name: TOTAL QUARTZ 9000 0W30

Product application: Motor oil

Company name: TOTALFINAELF LUBRIFIANTS

Address: 16, rue de la République

92800 PUTEAUX

FRANCE

Emergency number of the company : 33(1)41.35.40.00

Fax: 33 (1)41.35.84.71

See local particulars at end of sheet

Emergency phone numbers : - Centre anti-poisons : ORFILA (FRANCE): 33 (0) 1.45.42.59.59

2. Composition / information on ingredients

PREPARATION

Chemical nature: Product with a synthetic oil base

Subtances contributing to hazards : Zinc di-thiophosphate (Xi - R38 - R41) ... max 3%

Impurities contributing to hazards:

None to our knowledge

3. Hazard identification

- Adverse human health effects : Under normal conditions of use, the product holds no danger of intoxication

- Environmental effects : Don't rejet this product into the environment

- physical and chemical hazards : No specific risk of fire or explosion under normal contitions of use

4. First-aid measures

IN CASE OF SERIOUS MANIFESTATIONS, CALL IN A DOCTOR OR EMERGENCY MEDICAL CARE

Route of exposure:

- Inhalation : Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild irritation of the

throat.

Transport the person into fresh air, keep warm and allow to rest

TOTAL QUARTZ 9000 0W30

- Contact with the skin: Immediately remove all soiled or stained clothing

Wash the affected area immediately and repeatedly with soap and water.

- Contact with the eyes: Keep eyes open and rinse immediately and repeatedly with water for at least 15 minutes

- Ingestion : Possible risk of vomiting and diarrhoea

Do not induce vomiting to avoid the risk of aspiration into the respiratory tract

Page:2/7

Give nothing to drink

- Aspiration: If the product is believed to have entered the lungs (in case of vomiting, for example), take the

person to hospital for immediate care

5. Fire-fighting measures

Flash point: See heading 9

Fire extinguishers:

- suitable : Foam, carbon dioxide (CO2), powder

- not suitable : do not use water jets (stick jets) for extinguishing fire since they could help to spread the flames.

Specific hazards: Incomplete combustion and thermolysis produce toxic gases such as CO, CO2, various

hydrocarbons, aldehydes and soot. These are highly dangerous if inhaled

Firefighter protection: An insulated breathing apparatus must be worn in confined premises with heavy concentrations

of fumes and gases

6. Accidental release measures

See also heading 8 and 13 After spillage / leakage

- on soil Surfaces on which the product has been spilled may become slippery

Avoid discharge of the material in a stream or a sewer or cause ground contamination.

recovery by physical means

Contain and collect the spilled product with sand or any other inert material.

In the event of a major spill, inform the competent authorities if the situation cannot be brought

under control rapidly and efficiently

- on water Use floating absorbent material to be removed mechanically

If the material has been discharged into a stream or a sewer, inform the authorities of the

possible presence of floating materials

TOTAL QUARTZ 9000 0W30

7. Handling and storage

HANDLING

- Technical measures :

. prevention of user exposure Provide adequate ventilation in case of the potential formation of vapour, fumes, mist or spray

Take all measures to reduce the risk of exposure, in particular to used or waste product

Page:3/7

Keep away from flammable material; keep away from food and beverages

. Prevention of fire and explosion Empty containers may contain flammable or explosive vapours

There is a fire hazard associated with rags, paper or any other material used to remove spills

which become soaked with product

Avoid accumulate of these: they are to be disposed off safely after use

- Precautions : Avoid static electricity build up with connection to earth.

Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot

machine parts and electrical contacts (on joint failure, for example)

- Safe handling advice : Avoid contact with strong oxidizing agents

Use only hydrocarbon-resistant containers, joints, pipes etc...

STORAGE

- Technical measures: Make the necessary arrangements and take all measures to prevent water and ground pollution

- Storage conditions :

. Suitable Store at room temperature, protected against contact with water and moisture, and away from

any source of ignition

Keep containers closed when not in use

. To be avoided Do not store exposed to the elements
- Incompatible products : Dangerous reaction with strong oxidizing agents

- Packaging materials :

. Recommended Use only hydrocarbon-resistant containers, joints, pipes, etc.

Keep in original container if possible

Otherwise, transfer all indications on the regulatory label to the new container

8. Exposure controls / personal protection

Engineering measures:

Use the product in well-ventilated premises

When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is not

sufocating and/or wear recommend eqipment

Personal protective equipment

- Hand protection: Impermeable hydrocarbon-proof gloves

recommended material: nitrile, neoprene

- Eye protection: Goggles, in case of splashing

TOTAL QUARTZ 9000 0W30

Page:4/7

- Skin and body different hand protection: As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when handling

drums)

Don't wear ring, watch or similar thing which will be able to hold the product and may give rise

to some skin diseases

Industrial hygiene Avoid prolonged and repeated contact with the skin, especially with used or waste product

Immediately remove all soiled or stained clothing.

If the product comes into contact with the skin, wash the affected area immediately and

repeatedly with soap and water

Use no abrasives, solvents or petroleum spirit

Do not use cloths stained with the product to dry hands

Dont put the product-soaked rags in the pockets of working clothes

Do not eat, drink or smoke while handling the product

9. Physical and chemical properties

Appearance:

- Physical state: Clear liquid- Colour: Yellow to amber

Odour: Characteristic odour of oil

pH: Not applicable

Specific temperatures

of change in state

Flash point: >= 210°C (ISO 2592) Auto-ignition temperature: > 250°C (ASTM E 659)

This temperature may be significantly lower under particular conditions (oxidation on high

surface areas)

Explosion limits: Not applicable

Density: About 856kg/m3 at 15°C

Solubility:

- in water: Insoluble and immiscible

- in organic solvents: Soluble in many common solvents

- Viscosity: Kinematic viscosity at 100°C: about 9.8 mm²/s

10. Stability and reactivity

Stability: The product is stable under normal temperatures of storage, handling and use

Dangerous reactions: Not dangerous reaction known under normal conditions of use, to refer to the technical notice
- Conditions to avoid: Heat (temperatures above flash point), sparks, ignition points, flames, static electricity

TOTAL QUARTZ 9000 0W30

Date: 17/07/2000

Page:5/7

- Materials to avoid: Avoid contact with strong oxidizing

Dangerous decomposition products: Incomplete combustion and thermolysis produce more or less toxic gases such as CO, CO2,

various hydrocarbons, aldehydes and soot

11. Toxicological information

ACUTE TOXICITY/LOCAL EFFECTS

- Inhalation: Risk is improbable under normal conditions of use

Inhalation of important concentration of vapour or aerosols may cause irritation of the upper

respiratory tract.

- Contact with the skin: Risk is improbable under normal conditions of use

- Ingestion: In case of ingestion of small quantities, no important effect observed. in case of ingestion of

larger amounts: abdominal pain, diarrhoea, ...

SENSITIZATION To our knowledge, the product dont induce sensitization

CHRONIC TOXICITY OR LONG-TERM

TOXICITY

- Contact with the skin: Characteristic skin affections (oil blisters) may develop following prolonged and repeated

exposure through contact with stained clothing

- Carcinogenecity: During use in engines, contamination of oil with low levels of combustion products occurs.

Used motor oils have been shown to cause skin cancer in mice following repated application

and continuous exposure.

Brief or intermittent skin contact with used motor oil is not expected to have serious effects in

humans if the oil is thoroughly removed by washing with soap and water.

12. Ecological information

Mobility:

- Air: there is a slow loss by evaporation.

- Ground: Given its physical and chemical characteristics, the product generally shows little mobility in

the ground

- Water: The product is insoluble; it spreads on the surface of the water

Persistence and degradability: Experimental data on the finished product are not available

Ecotoxicity: The virgin product is considered to present no danger for land-growing organisms.

It is considered to present a little danger for aquatic life.

no information available for used product

TOTAL QUARTZ 9000 0W30

Date: 17/07/2000

Page:6/7

13. Disposal considerations

Waste disposal: Dispose in a safe manner in accordance with local/national regulations

If need be, collection by an authorized waste contractor and regeneration or incineration in an

approved installation

Used packaging disposal: Conform to the regulation in effect

Industrial waste number EU: 13-02-02 (non-chlorinated engine, gear, lubricating oils)

14. Transport information

UN Number: unregulated

Road (ADR) / Rail (RID)/ River (ADNR)

Marine (IMO-IMDG)

Not restricted for transport.

Airline (ICAO / IATA)

Not restricted for transport.

15. Regulatory information

EUROPEAN REGULATIONS

- EC labelling

- Symbol(s) None
- R Phrase(s) None
- S Phrase(s) None

16. Other information

This data sheet conforms to standards defined by directive 93/112/EEC

Date of current version: 17/07/2000

Supersedes previous Safety Data Sheet of:

Emergency phone numbers: +44.(0)171 635 91 91 / Nantional Poisons Information Service LONDON

+44 1222 70 99 01 / Welsh National Poisons Unit CARDIFF

+44 131 536 23 00 / Scottish Poisons Information Bureau EDINBURGH

+44 1 232 24 05 03 / Regional drug and poisons Information Service BELFAST

+353 1 837 99 64 / Poisons Information Centre DUBLIN

"This Safety Data Sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of ou knowledge at the date indicated hereabove.

It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk.

TOTAL QUARTZ 9000 0W30

Page:7/7

The information given herein in no way dispenses the user from knowing and applying all provisions regulating his or her activity. The user bears sole liability for the precautions required when using the product.

The regulatory texts indicated herein are intended to aid the user to fulfill his obligations. This list is not to be considered complete and exhaustive.

It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned."

End of document. Number of page(s):7