



Safety Data Sheet

Product Name: **QUARTZ 4X4**

Page: 1/5

SDS N° DXB/05/05/011

Version of: May 2005

PRODUCT LABELS

LABELLING (standard or EU): Not concerned
R-phrases : None
S-phrases : None
TRANSPORT LABELLING: Not applicable.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name of the product : **QUARTZ 4X4**
Product application : Gasoline & Diesel Engine oil
Supplier : **TOTAL LUBRICANTS MIDDLE EAST LLC**
Al Masaood Building - 7th Floor – 701
Airport Road – Dubai
U A E
Telephone: **+ 971 4 294 5 800**
Fax: **+ 971 4 294 0 447**

Emergency Telephone Number of the company during working hours : **+ 971 4 295 0 869**

2. COMPOSITION/INFORMATION ON INGREDIENTS

PREPARATION

Chemical nature : The product is made from synthetic base oils (Polyalphaolefins).

Substances presenting a health hazard	EC No.	CAS No.	Content	Symbol(s)	R-phrases
Zinc alkyl di thiophosphate		68649-42-3	<2 %	Xi ,N	R-38, 41, 51/53
Sulfonate de Calcium			<1 %	Xi	R-43, 52/53

See section 16 for explanations of R-phrases

3. HAZARDS IDENTIFICATION

Health effects : Under normal conditions of use, the product holds no danger of intoxication
Environmental impact : Do not rejeit this product into the environment
Physico-chemical hazards : No specific risk of fire or explosion under normal contitions of use

4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT MANIFESTATIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Inhalation : Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild irritation of the throat.
Transport the person into fresh air, keep warm and allow to rest.
Ingestion : Possible risk of vomiting and diarrhoea.
Do not induce vomiting to avoid the risk of aspiration into the respiratory tract.
Give nothing to drink



Safety Data Sheet

Product Name:

QUARTZ 4X4

Page: 2/5

SDS N° DXB/05/05/011

Version of: May 2005

Skin contact : Immediately remove all soiled or stained clothing.
Wash the affected area immediately and repeatedly with soap and water.

Eye contact : Keep eyes open and rinse immediately and repeatedly with water for at least 15 minutes.

Aspiration : If the product is believed to have entered the lungs (in case of vomiting, for example), take the person to hospital for immediate care.

5. FIRE FIGHTING MEASURES

Flash point:
See heading 9

Extinguishing media :
- suitable:
Foam, carbon dioxide (CO₂), powder.
- not recommended:
do not use water jets (stick jets) for extinguishing fire since they could help to spread the flames.

Specific hazards : Incomplete combustion and thermolysis produce gases of varying toxicity such as CO, CO₂, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled.

Protective measures for firefighters : Insulated breathing apparatus must be worn in confined premises with heavy concentrations of fumes and gases.

6. ACCIDENTAL RELEASE MEASURES

See sections 8 and 13.

After spillage / leakage :
- On the soil:
Surfaces on which the product has been spilled may become slippery.
Do not allow the product to enter sewers or rivers or contaminate the soil.
Recover with mechanical means such as pumps and skimmers.
- On water:
Floating absorbant material, then mechanical recovery.
If the product is spilled in a river or in the sewers, notify the authorities of the possible presence of floating items.

Spill cleanup methods :
- Recovery:
Use mechanical means such as pumps, skimmers and absorbent materials.
- Elimination:
Hand over contaminated materials to an approved collector - see also section 13.

7. HANDLING AND STORAGE

HANDLING :

Prevention of user exposure :
Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk.
Make all the necessary arrangements in order to reduce exposure risk, notably to products in use or to wastes.
Keep away from combustive substances; keep away from food and beverages.

Prevention of fire and explosion :
Empty containers may contain flammable or explosive vapours.
There is a fire hazard associated with rags, paper or any other material used to remove spills which become soaked with product.
Avoid accumulate of these: they are to be disposed off safely after use.

Precautions :
Avoid static electricity build up with connection to earth.
Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for example).



Safety Data Sheet

Product Name:

QUARTZ 4X4

Page: 3/5

SDS N° DXB/05/05/011

Version of: May 2005

STORAGE :

Technical measures :

Make the necessary arrangements to prevent water and soil pollution.

Storage precautions :

- Suitable:
Store at room temperature, protected against contact with water and moisture, and away from any source of ignition.
Keep containers closed when not in use
- To be avoided:
Do not store exposed to the elements.

Incompatible products :

Dangerous reaction with strong oxidizing agents.

Packaging materials :

- Recommended:
Use only hydrocarbon-resistant containers, joints, pipes, etc.
Keep in original container if possible.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Technical measures :

Use the product in a properly ventilated atmosphere.
When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is not suffocating and/or wear recommend equipment.

Occupational exposure limit :

. oil mist : 10mg/m³, for 15 minutes
. oil mist : 5mg/m³, for 8 hours

Hand protection :

Impermeable hydrocarbon-proof gloves.
recommended material: nitrile , neoprene.

Eye protection :

Goggles, in case of risk of splashing.

Skin and body (other than the hands) protection :

As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when handling drums).
Don't wear ring, watch or similar thing which will be able to hold the product and may give rise to some skin diseases.

Hygienic work practices :

Avoid prolonged and repeated contact with the skin, especially with used or waste Product.
Immediately remove all soiled or stained clothing.
If the product comes into contact with the skin, wash the affected area immediately and copiously with soap and water.
Use no abrasives, solvents or fuels.
Do not use cloths stained with the product to dry hands.
Do not put the product-soaked rags in the pockets of working clothes.
Do not eat, drink or smoke while handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance :

Liquid.

Colour :

Yellow to amber.

Odour :

Characteristic.

Density/specific gravity :

878 kg/m³
Temperature (°C) 15

Flash point :

> 230 ° C

Auto ignition point :

> 250 ° C (ASTM E 659)

Comments on autoignition temperature :
oxidation on finely divided materials...).

This temperature may be significantly lower under particular conditions (slow

Solubility :

Insoluble in water.
Soluble in many common solvents.



Safety Data Sheet

Product Name:

QUARTZ 4X4

Page: 4/5

SDS N° DXB/05/05/011

Version of: May 2005

Partition coefficient (log Pow) :

Log Pow > 6
Temperature (°C) 20

Viscosity :

18.50 mm²/s
Temperature (°C) 100

10. STABILITY AND REACTIVITY

Stability :

The product is stable at normal storage, handling and use temperatures.

Conditions to avoid :

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity

Materials to avoid :

Avoid contact with strong oxidizers

Hazardous decomp. products :

Incomplete combustion and thermolysis produce more or less toxic gases such as CO, CO₂, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

Acute toxicity / Local effect :

Inhalation, comments:

Risk is improbable under normal conditions of use
Inhalation of important concentration of vapour or aerosols may cause irritation of the upper respiratory tract.

Skin contact, comments:

Risk is improbable under normal conditions of use.

Ingestion, comments:

In case of ingestion of small quantities, no important effect observed. in case of ingestion of larger amounts: abdominal pain, diarrhea, ...

CHRONIC TOXICITY OR LONG-TERM TOXICITY :

Skin contact :

Characteristic skin affections (oil blisters) may develop following prolonged and repeated exposure through contact with stained clothing

Sensitization :

To our knowledge, the product does not cause aggravated sensitivity.

Carcinogenicity :

During use in engines, contamination of oil with low levels of combustion products occurs.
Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure.
Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

12. ECOLOGICAL INFORMATION

Comments about ecotoxicity :

Experimental data on the finished product are not available.
It is considered to present a little danger for aquatic life.
no information available for used product

Mobility :

- Air:
there is a slow loss by evaporation.
- Soil:
Given its physical and chemical characteristics, the product generally shows little mobility in the ground.
- Water:
The product is insoluble; it spreads on the surface of the water

Persistence and degradability :

No experimental information about the finished product.
The product should offer slow biodegradability



Safety Data Sheet

Product Name:

QUARTZ 4X4

Page: 5/5

SDS N° DXB/05/05/011

Version of: May 2005

DISPOSAL CONSIDERATIONS

Waste disposal :

Dispose of in a safe manner, in accordance with local regulations.
If need be, collection by an authorized waste contractor and regeneration or incineration in an approved installation

Waste class :

13 02 05

Disposal of contaminated packaging :

Proceed in compliance with the prevailing regulations.

13. TRANSPORT INFORMATION

Not concerned by the transport regulations below.

Road (ADR) / Rail (RID) :

Transport by barge (ADNR) :

Marine (IMO-IMDG) :

Air (ICAO/IATA) :

14. REGULATORY INFORMATION

Risk phrases :

None

Safety phrases :

None

Other :

- Contains:
Long chain calcium sulphonate.
Can start an allergic reaction.

EU directives :

Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC).

Social Security code :

- Art. L 461-6, Art. D 461-1, appendix A, No. 601.
Table of occupational illnesses and diseases No. 36

Labor code :

- Art. R 241-50, decree of 07.11.1977.

15. OTHER INFORMATION

Explanations of R-phrases in section 2 :

R-38 Irritating to skin.
R-41 Risk of serious damage to eye.
R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R-43 May cause sensitization by skin contact.
R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfill his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.