



MULTIS EP 2



Multipurpose grease with extreme-pressure properties

APPLICATIONS

Multipurpose EP greases,
general lubrication

Recommendation

- **MULTIS EP2** is a multipurpose grease specially formulated for lubricating bearings, smooth journals and standard seals in chassis and systems that are exposed to shock and vibration.
- Applications in all fields, regardless of the presence of water and dust.
- Preferably apply the grease using a pneumatic pump or cartridge system.

PERFORMANCE

- ISO 6743-9: L-XBCEB 2
- DIN 51 502: KP2K -25

CLIENT ADVANTAGES

Persistent lubricant film in
service,

Miscibility,
Mechanical stability

No harmful ingredients

- The multipurpose character of **MULTIS EP2** covers a wide range of applications and can replace many other greases making it possible to rationalise and simplify maintenance operations.
- The lubricant film is very persistent in service, reducing maintenance costs and outage times.
- Miscible with most conventional greases.
- Very good mechanical stability, preventing any discharge or loss of consistency in service.
- Excellent adhesion to metals.
- Good thermal stability, very good resistance to temperature changes.
- **MULTIS EP2** contains no lead or other heavy metal regarded as harmful to human health or the environment.

CHARACTERISTICS

	METHODS	UNITS	MULTIS EP2
Thickener		-	Lithium/Calcium
NLGI Grade	ASTM D 217/DIN 51 818	-	2
Colour	Visual	-	Light brown
Appearance	Visual	-	Smooth
Operating temperature range		°C	-25 to 120

The characteristics shown in this table are typical values provided for illustrative purposes.

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX (France)

Multis EP 2
October 2003



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazard. A safety data sheet complying with current EC legislation can be obtained from your local sales representative.