

Product name: MULTIS COMPLEX S 2 A Page : 1/6

SDS n°:34105-33 Version:1.00 Version of:2004-06-29

PRODUCT LABELS

LABELLING (standard or EU): Not concerned

R-phrases: None S-phrases: None

TRANSPORT LABELLING: Not applicable.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name of the product: MULTIS COMPLEX S 2 A

Code No.: KXX

Product application : Lubricating grease

Supplier: TOTAL LUBRIFIANTS

Le Diamant B

16, rue de la République 92922 Paris La Défense - France Tel: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

Emergency telephones: ORFILA / Tel: 01.45.42.59.59

See local details at end of sheet:

2. COMPOSITION/INFORMATION ON INGREDIENTS

PREPARATION

Chemical nature: The product is made from refined mineral base oils and synthetic oils in which the

polycyclic aromatic hydrocarbons (PCA or P14) content, measured by IP 346, is

less than 3%.

Substances presenting a health hazard	EC No.	CAS No.	Content	Symbol(s)	R-phrases
Alkylated diphenylamines		68411-46-1	<1,5 %	N	R-51/53

See section 16 for explanations of R-phrases :

3. HAZARDS IDENTIFICATION

Health effects: None known to us for normal use.

Environmental impact : Do not release this product into the environment.

Physico-chemical hazards: No specific risk of fire or explosion under normal contitions of use

4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT MANIFESTATIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Inhalation: Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild

irritation of the throat.

Transport the person into fresh air, keep warm and allow to rest.

Ingestion : Possible risk of vomiting and diarrhoea.

Do not induce vomiting to avoid the risk of aspiration into the respiratory tract.



Product name: MULTIS COMPLEX S 2 A Page: 2/6

SDS n°:34105-33 Version:1.00 Version of:2004-06-29

Skin contact: Immediately remove all soiled or stained clothing.

Wash the affected area immediately and repeatedly with soap and water. If the skin is exposed to high-pressure spray, the product may enter the human organism. In all such cases the affected person must be taken to hospital, even if no

sign of injury can be detected.

Eye contact: Keep eyes open and rinse immediately and repeatedly with water for at least 15

minutes.

5. FIRE FIGHTING MEASURES

Flash point: See heading 9

Extinguishing media: - suitable:

Foam, carbon dioxide (CO2), powder.

- not recommended:

do not use water jets (stick jets) for extinguishing fire since they could help to

spread the flames.

Specific hazards: Incomplete combustion and thermolysis produce gases of varying toxicity such as

CO, CO2, various hydrocarbons, aldehydes and soot. These may be highly

dangerous if inhaled.

Protective measures for firefighters: Insulated breathing apparatus must be worn in confined premises with heavy

concentrations of fumes and gases.

6. ACCIDENTAL RELEASE MEASURES

See sections 8 and 13.

After spillage / leakage : - On the soil:

Surfaces on which the product has been spilled may become slippery. Do not allow the product to enter sewers or rivers or contaminate the soil.

Recover with mechanical means such as pumps and skimmers.

Contain and collect the spilled product with sand or any other inert absorbant

material.

In case of spillage, contact the competent authorities if the situation cannot be

brought under control rapidly and efficiently.

- On water:

Floating absorbant material, then mechanical recovery.

If the product is spilled in a river or in the sewers, notify the authorities of the

possible presence of floating items.

7. HANDLING AND STORAGE

HANDLING:

Prevention of user exposure: Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk.

Make all the necessary arrangements in order to reduce exposure risk, notably to

products in use or to wastes.

 $\label{thm:combustible} Keep\ away\ from\ food\ and\ beverages.$

Prevention of fire and explosion: Empty containers may contain flammable or explosive vapours.

There is a fire hazard associated with rags, paper or any other material used to

remove spills which become soaked with product.

Avoid accumulate of these: they are to be disposed off safely after use.

Precautions: Avoid static electricity build up with connection to earth.

Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for

example).

STORAGE:



Product name: MULTIS COMPLEX S 2 A Page : 3/6

SDS n°:34105-33 Version:1.00 Version of:2004-06-29

Technical measures: Make the necessary arrangements to prevent water and soil pollution.

Storage precautions : - Suitable:

Store at room temperature, protected against contact with water and moisture, and

away from any source of ignition.

Keep containers closed when not in use

- To be avoided:

Do not store exposed to the elements.

Incompatible products: Dangerous reaction with strong oxidizing agents.

Packaging materials : - Recommended:

Use only hydrocarbon-resistant containers, joints, pipes, etc.

Keep in original container if possible.

Otherwise, transfer all indications on the regulatory label to the new container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Technical measures: Use the product in a properly ventilated atmosphere.

When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is

not sufocating and/or wear recommend equipment.

. oil mist : 5mg/m3, for 8 hours

Hand protection: The dermands on the gloves are determined by the condition in practice (f.e.

multiple use, mechanical load, temperature, strengh and duration of exposition). Before choosing suitable gloves, it is recommended for the user to test the gloves. The breaking-through times of the same type of glove of different manufacturers can be very different - even if the layer thickness is similar. Therefore the

breaking-through times have to be found out by the manufacturer of the protection

gloves himself.

Impermeable hydrocarbon-proof gloves. recommended material: nitrile, neoprene.

Eye protection: Goggles, in case of risk of splashing.

Skin and body (other than the hands) protection : As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when

nandling drums).

Don't wear ring, watch or similar thing which will be able to hold the product and

may give rise to some skin diseases.

Hygienic work practices: Avoid prolonged and repeated contact with the skin, especially with used or waste

roduct

Immediately remove all soiled or stained clothing.

If the product comes into contact with the skin, wash the affected area immediately

and copiously with soap and water. Use no abrasives, solvents or fuels.

Do not use cloths stained with the product to dry hands.

Dont put the product-soaked rags in the pockets of working clothes.

Do not eat, drink or smoke while handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Pasty

Colour : Blue.

Odour : Characteristic

Density/specific gravity : 900 kg/m3

Temperature (°C) 15

Comments on flash points: Not applicable



Product name: MULTIS COMPLEX S 2 A Page : 4/6

SDS n° :34105-33 Version :1.00 Version of :2004-06-29

Température d'auto-inflammation : > 250 ° C (ASTM E 659)

Comments on autoignition temperature: This temperature may be significantly lower under particular conditions (slow

oxidation on finely divided materials...).

Comments on explosivity: Not applicable

Drop point: > 250 ° C (NF T 60-102)

Solubility: - in water:

Insoluble and immiscible. - in organic solvents :

Soluble in many common solvents.

Partition coefficient (log Pow): Log Pow > 6

Temperature (°C) (20°C)

Penetration index : 280 (1/10 mm) at 25°C according to ISO 2137

10. STABILITY AND REACTIVITY

Stability: The product is stable at normal storage, handling and use temperatures.

Conditions to avoid: Heat, sparks, ignition points, flames, static electricity.

Materials to avoid: Avoid contact with strong oxidizers

Hazardous decomp. products: Incomplete combustion and thermolysis produce more or less toxic gases such as

CO, CO2, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

Acute toxicity / Local effect :

Inhalation, comments: Risk is improbable under normal conditions of use

Inhalation of important concentration of vapour or aerosols may cause irritation of

the upper respiratory tract.

Skin contact, comments: Risk is improbable under normal conditions of use.

If the skin is exposed to high-pressure spray, the product may enter the human organism. In all such cases the affected person must be taken to hospital, even if no

sign of injury can be detected

In case of ingestion of small quantities, no important effect observed. in case of

ingestion of larger amounts: abdominal pain, diarrhea, ...

CHRONIC TOXICITY OR LONG-TERM TOXICITY:

Skin contact: Characteristic skin affections (oil blisters) may develop following prolonged and

repeated exposure through contact with stained clothing

Sensitization: To our knowledge, the product does not cause aggravated sensitivity.

12. ECOLOGICAL INFORMATION

Comments about ecotoxicity: Experimental data on the finished product are not available.

It is considered to present a little danger for aquatic life.

no information available for used product

Mobility: - Ai

there is a slow loss by evaporation.

- Soil:

Given its physical and chemical characteristics, the product has no soil mobility.

Water:

The product is insoluble; it spreads on the surface of the water



Product name: MULTIS COMPLEX S 2 A Page: 5/6

SDS n°:34105-33 Version:1.00 Version of:2004-06-29

Persistence and degradability: No experimental information about the finished product.

However the "mineral oil" fraction of the new product is intrinsically biodegradable.

13. DISPOSAL CONSIDERATIONS

Waste disposal: Dispose of in a safe manner, in accordance with local regulations.

If need be, collection by an authorized waste contractor and regeneration or

incineration in an approved installation

Waste class: The waste key mentioned here represents only a recommendation. Responsible for

the correct specification of the waste key is the waste producer. The specification of the waste key should be in arrangement with the responsible waste disposer. The waste key is depending on the composition of the product at the time of

disposal. 12 01 12

Disposal of contaminated packaging: Proceed in compliance with the prevailing regulations.

National regulations : - France

List of wastes: JOCE L349 of 16.02.2001.

Law No. 75-633 of 15.07.75 amended, relative to the elimination of wastes and the

recovery of materials.

Regulations concerning the collection of used oils:

Decree 79-981 of 21.11.79 and rules of 28.01.99 relative to their collection and the

conditions for their elimination.

Law No. 88-1261 of 30.12.88 concerning the import, export and transit of wastes. Decree No. 77-254 of 08.03.77 relative to the regulation for the dumping of oils and

lubricants into surface waters.

14. TRANSPORT INFORMATION

Not concerned by the transport regulations below.

Road (ADR) / Rail (RID):

Transport by barge (ADNR):

Marine (IMO-IMDG):

Air (ICAO/IATA):

15. REGULATORY INFORMATION

Not applicable

Risk phrases : None
Safety phrases : None

EU directives: Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC).

Social Security code : Table of occupational illnesses and diseases No. 36, No. 4 bis - Art. L.461-6, Art. D.461-1, apendix A, No. 601, No. 15

Labor code: - Art. R 241-50, decree of 07.11.1977.

16. OTHER INFORMATION

For France, in case of poisoning call the Antipoison Centre (if possible in your area) and/or the SAMU (15), see ORFILA number below - Tel: Angers 02.41.48.21.21 - Bordeaux 05.56.96.40.80 - Lille 03.20.44.44.44 - Lyon 04.72.11.69.11 - Marseille 04.91.75.25.25 - Nancy 03.83.32.36.36 - Paris 01.40.05.48.48 - Rennes 02.99.59.22.22 - Strasbourg 03.88.37.37.37 - Toulouse 05.61.77.74.47 This sheet is in compliance with the standarts defined by the directives 91/155/CEE, 93/112/CEE, 2001/58/CE and the article 14 of the directive 1999/45/EC.



Product name: MULTIS COMPLEX S 2 A Page : 6/6

SDS n° :34105-33 Version :1.00 Version of :2004-06-29

Explanations of R-phrases in section 2 :

R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Revision date:

2004-06-29

* Information revised since the previous version of the SDS:

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.