


HYDRAURINCAGE



SPECIAL FLUID FOR FLUSHING OF HYDRAULIC SYSTEMS

USES

- TOTAL HYDRAURINCAGE is recommended when sticking or contamination has occurred in passenger car hydraulic systems filled with green mineral hydraulic fluid.

Never use TOTAL HYDRAURINCAGE in systems using synthetic brake fluids.

Handling instructions :

- Drain the system as much as possible.
- Fill the system with TOTAL HYDRAURINCAGE.
- Drive the car for at least 1500 km but maximum 5000 km.
- Drain and refill with TOTAL LHM PLUS

PROPERTIES

- The detergent action will dissolve the deposits which appear in hydraulic systems.

- Compatible with TOTAL LHM PLUS or all other hydraulic mineral fluid.

CHARACTERISTICS

HYDRAURINCAGE	Units	
Volumetric mass at 15°C	kg/m ³	851
Viscosity at -40°C	mm ² /s	< 5200
Viscosity at 40°C	mm ² /s	18
Viscosity at 100°C	mm ² /s	5
Viscosity index	-	211
Pour point	°C	- 62

The typical characteristics mentioned represent mean values.

SPECIFICATIONS

PSA PEUGEOT CITROËN

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX

HYDRAURINCAGE
November 2003



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.