

| Product: | TOTAL TRANSMISSION X4 80W90 | | |
|--|--|---|--|
| | | Page: 1/5 | |
| Product code: 07X-0J2YUJF-26 | Issue : 4 | Date: 2002-06-14 Invalidates and replaces the issue of : 1999-06-07 | |
| PRODUCT LABELS | | | |
| LABELLING (standard or EU): | Not applicable | | |
| TRANSPORT LABELLING : | Not applicable | | |
| 1. Product and company identification | | | |
| Commercial name: | TOTAL TRANSMISSION X4 80W90 | | |
| Product application: | Oil for limited slip differentials, conventional | axles and transfer boxes | |
| Company name: | Total Fina Elf Lubrifiants | | |
| Address: | 16, rue de la République 92800 PUTEAUX FRANCE | | |
| Emergency number of the company : | 33 (1)41.35.40.00 | | |
| Fax: | 33 (1)41.35.84.71 | | |
| See local particulars at end of sheet: | | | |
| Emergency phone numbers : | - Centre anti-poisons : ORFILA (FRANCE): | 33 (0) 1.45.42.59.59 | |
| 2. Composition / information on ingredie | nts | | |
| PREPARATION: | | | |
| Chemical nature: | | Petroleum-derived severely refined mineral-base product in which the polycyclic aromatic hydrocarbons (PCA or PAH) content, measured by IP 346, is less than 3% | |
| Subtances contributing to hazards : | None to our knowledge, in normal use | None to our knowledge, in normal use | |
| 3. Hazard identification | | | |
| - Adverse human health effects : | Under normal conditions of use, the product h | nolds no danger of intoxication | |
| - Environmental effects : | Don't rejet this product into the environment | Don't rejet this product into the environment | |
| - physical and chemical hazards : | No specific risk of fire or explosion under nor | rmal contitions of use | |
| 4. First-aid measures | | | |
| IN CASE OF SERIOUS MANIFESTATIONS | S, CALL IN A DOCTOR OR EMERGENCY MEDICA | AL CARE | |
| Route of exposure : | | | |
| - Inhalation : | Inhalation of heavy concentrations of vapour, throat. Transport the person into fresh air, keep warm | fumes or spray, may cause mild irritation of the | |
| - Contact with the skin : | Immediately remove all soiled or stained cloth | Immediately remove all soiled or stained clothing Wash the affected area immediately and repeatedly with soap and water. | |
| - Contact with the eyes : | | Keep eyes open and rinse immediately and repeatedly with water for at least 15 minutes | |

TOTAL LUBRIFIANTS

16, rue de la République 92922 PUTEAUX FRANCE



Safety Data Sheet Product: TOTAL TRANSMISSION X4 80W90 Page: 2/5 Product code: 07X-0J2YUJF-26 Issue: 4 Date: 2002-06-14 Invalidates and replaces the issue of : 1999-06-07 - Ingestion : Possible risk of vomiting and diarrhoea Do not induce vomiting to avoid the risk of aspiration into the respiratory tract Give nothing to drink If the product is believed to have entered the lungs (in case of vomiting, for example), take the - Aspiration : person to hospital for immediate care 5. Fire-fighting measures Flash point: See heading 9 Fire extinguishers: - suitable : Foam, carbon dioxide (CO2), powder - not suitable : do not use water jets (stick jets) for extinguishing fire since they could help to spread the flames. Specific hazards: Incomplete combustion and thermolysis produce toxic gases such as CO, CO2, various hydrocarbons, aldehydes and soot. These are highly dangerous if inhaled Firefighter protection: An insulated breathing apparatus must be worn in confined premises with heavy concentrations of fumes and gases 6. Accidental release measures See also heading 8 and 13: After spillage / leakage: Surfaces on which the product has been spilled may become slippery - on soil: Avoid discharge of the material in a stream or a sewer or cause ground contamination. recovery by physical means Contain and collect the spilled product with sand or any other inert material. In the event of a major spill, inform the competent authorities if the situation cannot be brought under control rapidly and efficiently

7. Handling and storage

HANDLING:

- on water:

| - Technical measures : | |
|-------------------------------------|--|
| . prevention of user exposure: | Provide adequate ventilation in case of the potential formation of vapour, fumes, mist or spray Take all measures to reduce the risk of exposure, in particular to used or waste product Keep away from flammable material; keep away from food and beverages |
| . Prevention of fire and explosion: | Empty containers may contain flammable or explosive vapours There is a fire hazard associated with rags, paper or any other material used to remove spills which become soaked with product Avoid accumulate of these: they are to be disposed off safely after use |
| - Precautions : | Avoid static electricity build up with connection to earth. Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for example) |
| - Safe handling advice : | Avoid contact with strong oxidizing agents Use only hydrocarbon-resistant containers, joints, pipes etc |
| STORAGE: | |
| TOTAL LUBRIFIANTS | 16, rue de la République 92922 PUTEAUX FRANCE |

presence of floating materials

Use floating absorbent material to be removed mechanically

If the material has been discharged into a stream or a sewer, inform the authorities of the possible



Safety Data Sheet

| Product: TOTAL TRANSMISSION X4 80W90 | | | |
|--|---|--|--|
| Product code: 07X-0J2YUJF-26 | Issue : 4 Invalidates and rep | Date: 2002-06-14 blaces the issue of : 1999-06-07 | |
| - Technical measures : | Make the necessary arrangements and take all measures to prevent | water and ground pollution | |
| - Storage conditions : | | | |
| . Suitable: | Store at room temperature, protected against contact with water and moisture, and away from any source of ignition Keep containers closed when not in use | | |
| . To be avoided: | Do not store exposed to the elements | | |
| - Incompatible products : | Dangerous reaction with strong oxidizing agents | Dangerous reaction with strong oxidizing agents | |
| - Packaging materials : | | | |
| . Recommended: | Use only hydrocarbon-resistant containers, joints, pipes, etc. Keep in original container if possible Otherwise, transfer all indications on the regulatory label to the new container | | |
| 8. Exposure controls / personal protection | | | |
| Engineering measures: | Use the product in well-ventilated premises When working on enclosed place (tanks, reservoirs), make sure that atmosphere is not sufocating and/or wear recommend eqipment | | |
| - Control parameters: | | | |
| . Occupational exposure limit: | . oil mist : 10mg/m3, for 15 minutes . oil mist : 5mg/m3, for 8 hours | | |
| Personal protective equipment: | | | |
| - Hand protection: | Impermeable hydrocarbon-proof gloves recommended material: nitrile, neoprene | | |
| - Eye protection: | Goggles, in case of splashing | | |
| - Skin and body different hand protection: | As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when handling drums) Don't wear ring, watch or similar thing which will be able to hold the product and may give rise to some skin diseases | | |
| Industrial hygiene: | Avoid prolonged and repeated contact with the skin, especially with Immediately remove all soiled or stained clothing. If the product comes into contact with the skin, wash the affected ar with soap and water Use no abrasives, solvents or petroleum spirit Do not use cloths stained with the product to dry hands Dont put the product-soaked rags in the pockets of working clothes Do not eat, drink or smoke while handling the product | rea immediately and repeatedly | |

9. Physical and chemical properties

| Appearance: | |
|------------------------|---|
| - Physical state: | Clear to slightly cloudy liquid |
| - Colour: | Brown |
| Odour: | Characteristic odour of oil |
| pH: | Not applicable |
| Specific temperatures: | of change in state |
| Flash point: | >= 160°C (ISO 2592) |
| TOTAL LUBRIFIANTS | 16, rue de la République 92922 PUTEAUX FRANCE |



Safety Data Sheet **TOTAL TRANSMISSION X4 80W90 Product:** Page: 4/5 Product code: 07X-0J2YUJF-26 Issue: 4 Date: 2002-06-14 Invalidates and replaces the issue of : 1999-06-07 > 250°C (ASTM E 659) Auto-ignition temperature: This temperature may be significantly lower under particular conditions (oxidation on high surface areas) **Explosion limits:** Not applicable Density: About 896 kg/m3 at 15°C Solubility: Insoluble and immiscible - in water: Soluble in many common solvents - in organic solvents: - Viscosity: Kinematic viscosity at 100°C: about 18 mm²/s Log P n-octanol / water at 20°C: mineral oil > 6 10. Stability and reactivity Stability: The product is stable under normal temperatures of storage, handling and use Not dangerous reaction known under normal conditions of use, to refer to the technical notice Dangerous reactions: - Conditions to avoid: Heat (temperatures above flash point), sparks, ignition points, flames, static electricity - Materials to avoid: Avoid contact with strong oxidizing Incomplete combustion and thermolysis produce more or less toxic gases such as CO, CO2, Dangerous decomposition products: various hydrocarbons, aldehydes and soot 11. Toxicological information ACUTE TOXICITY/LOCAL EFFECTS: - Inhalation: Risk is improbable under normal conditions of use Inhalation of important concentration of vapour or aerosols may cause irritation of the upper respiratory tract. Risk is improbable under normal conditions of use - Contact with the skin: - Ingestion: In case of ingestion of small quantities, no important effect observed. in case of ingestion of larger amounts: abdominal pain, diarrhoea, ... SENSITIZATION: To our knowledge, the product dont induce sensitization CHRONIC TOXICITY OR LONG-TERM TOXICITY:

- Contact with the skin:

12. Ecological information

| Mobility: | |
|-----------|--|
| - Air: | there is a slow loss by evaporation. |
| - Ground: | Given its physical and chemical characteristics, the product generally shows little mobility in the ground |
| - Water: | The product is insoluble; it spreads on the surface of the water |
| | |

exposure through contact with stained clothing

Characteristic skin affections (oil blisters) may develop following prolonged and repeated

TOTAL LUBRIFIANTS

16, rue de la République 92922 PUTEAUX FRANCE



| IOTAL | Safety Data Sheet | | |
|--|--|---|--|
| Product: | TOTAL TRANSMISSION X4 80W90 | Page: 5/ | |
| Product code: 07X-0J2YUJF-26 | Issue : 4 Invalidates and | Date: 2002-06-1- l replaces the issue of : 1999-06-0 | |
| Persistence and degradability: | Experimental data on the finished product are not available However, the "mineral oil" portion of the virgin product is intrinsically biodegradable. Particular ingredients may not be biodegradable | | |
| Ecotoxicity: | The virgin product is considered to present no danger for land-growing organisms. It is considered to present a little danger for aquatic life. no information available for used product | | |
| 13. Disposal considerations | | | |
| Waste disposal : | Dispose in a safe manner in accordance with local/national regulations If need be, collection by an authorized waste contractor and regeneration or incineration in an approved installation | | |
| Used packaging disposal : | Conform to the regulation in effect | Conform to the regulation in effect | |
| Industrial waste number EU : | 13-02-02 (non-chlorinated engine, gear, lubricating oils) | 13-02-02 (non-chlorinated engine, gear, lubricating oils) | |
| 14. Transport information | | | |
| UN Number : | unregulated | unregulated | |
| Road (ADR) / Rail (RID)/ River (ADNR): | Not restricted for transport. | | |
| Marine (IMO-IMDG): | Not restricted for transport. | | |
| Airline (ICAO / IATA): | Not restricted for transport | | |
| 15. Regulatory information | | | |
| EUROPEAN REGULATIONS: | | | |
| - EC labelling: | | | |
| - Symbol(s): | None | | |
| - R Phrase(s): | None | None | |
| - S Phrase(s): | None | | |

This data sheet conforms to standards defined by directives 91/155, 93/112/EEC & 2001/58/EC Data sheet required pursuant to Art.14 of directive1999/45/EC.

| Date of current version: | 14/06/2002 |
|---|------------|
| Supersedes previous Safety Data Sheet of: | 07/06/1999 |

"This Safety Data Sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of ou knowledgeat the date indicated hereabove.

It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk.

The information given herein in no way dispenses the user from knowing and applying all provisions regulating his or her activity. The user bears sole liability for the precautions required when using the product.

The regulatory texts indicated herein are intended to aid the user to fulfill his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned."

End of document. Number of page(s): 5

TOTAL LUBRIFIANTS